



AKVATOP

SEMI-MATT WATER-BASED PAINT FOR WOODEN FACADES



- Long lasting decorative effect
- Long term protection of painted surface from cracking or peeling
- Effectively protects wood against weather conditions even in extreme climatic conditions.

DESCRIPTION:

Water-based acrylic paint with high resistance to atmospheric influence. Increased flexibility of film completely prevents cracking and peeling of coating due to the impact of atmospheric agents, ensuring long lasting effect. The paint is characterised by great spreading capacity; it does not drip during the application. May be tinted in to a broad variety of shades.

FIELD OF APPLICATION:

Paint is intended for painting of exterior wooden walls and other wooden surfaces exposed to atmosphere.

| <u>TECHNICAL PARAMETERS:</u> | |
|--|---|
| <u>Colour:</u> | Produced in ready to use colors: White (A base), reddish-brown, dark-brown, yellow, dark-green, black and mustard. White (A base) may be tinted to light shades, C base – to dark shades, using RILAKOLOR tinting system. |
| <u>Gloss:</u> | Semi-matt |
| <u>Drying time at 20°C temperature:</u> | 1±1.5 hours, depending on shade. |
| <u>Consumption:</u> | 8÷11 m ² /l for one layer. |
| <u>Solvent:</u> | Water. |
| <u>Tools used for application:</u> | Brush, roller, airbrush. |
| <u>Storage period:</u> | 36 months in tightly closed manufacturer's container at the temperature exceeding +5°C. |
| <u>Packaging:</u> | 0.9 l; 3.6 l; 9 l. |

APPLICATION:

PREPARATION OF PAINT FOR USE:

Mix paint well before application. Dilute with water till required viscosity, if necessary.



PREPARATION OF SURFACE:

Remove dirt and dust from the surfaces to be painted. If the paint is applied on previously painted surfaces, you need to test a small area for verification of intercoat adhesion. Light sanding of surface to be painted with fine sandpaper is recommended for improving of intercoat adhesion.

PRIMING OF SURFACE:

Wooden surfaces intended for use in open environments prior to application of AKVATOP must be primed with colourless semi-transparent alkyd paint - TEKSTURDEKOR or TEKSTURDEKOR BASE.

APPLICATION:

Paint is applied on to clean, dry surfaces in 1-2 layers with a brush, roller or spray gum. During the application and 24 hours after that, temperature of air and painted surface must not be lower than +5°C, while relative air humidity must not be higher than 85%.

TOOL CLEANING:

Use water for cleaning of tools.

ENVIRONMENT AND OCCUPATIONAL SAFETY AND HEALTH PROTECTION:

Harmful to aquatic life with long lasting effects. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Avoid release to the environment. Dispose of contents and container in accordance with all local, regional, national or international regulations.



0.9l, 3.6l, 9l



8÷11 m²/l



1 h



RILAKOLOR
(A, C BASE)

