



# PENTAPRIM

## UNIVERSAL ALKYD ENAMEL FOR WOOD AND METAL



- May be used for interior and exterior works
- 25 ready shades
- For wood and metal

### **DESCRIPTION:**

Easy-to-apply universal gloss paint with excellent adhesion to various substrates, including new and previously painted metal and wooden surfaces. Enamel is characterised by long lasting gloss, good mechanical resistance.

### **FIELD OF APPLICATION:**

Paint is intended for painting of wooden, primed metal surfaces, wooden-fibre and particleboards both during interior and exterior works. May be used for painting of various wooden and metal objects and structures. In interior decoration works may be also used for painting of dry mineral surfaces - concrete, plaster and brick.

| <b><u>TECHNICAL PARAMETERS:</u></b>            |  |
|--|--|
| <b><u>Colour:</u></b>                          | Total number of ready shades – 25.<br>(white, red, orange, yellow, green, light-blue, blue, violet, ivory, cream, salmon, beige, terracotta, yellow-brown, red-brown, brown, cherry, sky-blue, saladgreen, light-green, turquoise, khaki, light-grey, grey, black) |
| <b><u>Gloss:</u></b>                           | Gloss  |
| <b><u>Drying time at 20°C temperature:</u></b> | Not more than 24 hours.  |
| <b><u>Consumption:</u></b>                     | 8÷11 m <sup>2</sup> /l for one layer.  |
| <b><u>Solvent:</u></b>                         | White spirit, VAITSOL  |
| <b><u>Tools used for application:</u></b>      | Brush, roller, paint sprayer.  |
| <b><u>Storage period:</u></b>                  | 36 months in tightly closed manufacturer's container at the temperature exceeding 0°C.   |
| <b><u>Packaging:</u></b>                       | 0.45 l; 0.9 l; 2.7 l; 10 l; 23 l.  |



## **APPLICATION:**

### **PREPARATION OF PAINT FOR USE:**

Mix paint well before application. If necessary, dilute with solvent till required viscosity using solvent up to 5% of the volume if applied by brush or roller.

### **PREPARATION OF SURFACE:**

Remove dust, various dirt contaminants and flakes paint. Remove rust from the metal surfaces. Sand glossy surfaces with sandpaper until light-matte appearance is reached.

### **PRIMING OF SURFACE:**

For priming of steel surfaces, we recommend to use the primers GF-021, NOVAKOR, NEOSPRINT PRIMER, RIATOP PRIMER. Treat aluminium and zinc-galvanized surfaces with primers VL-02 or NEOSPRINT PRIMER.

For new wooden surfaces intended to be used in open environment: Before painting, treat them with colour less TEKSTURDEKOR or TEKSTURDEKOR BASE.

### **APPLICATION:**

Apply paint on to clean and dry surfaces in 1–2 layers. Air temperature during painting and drying of paint may not be lower than + 5°C. Relative air humidity - not higher than 85%. Drying time of each layer – not longer than 24 hours.

### **TOOL CLEANING:**

Use white spirit or VAITSOL solvent for cleaning of tools.

### **ENVIRONMENT AND OCCUPATIONAL SAFETY AND HEALTH PROTECTION:**

**Contains** White Spirit. Flammable liquid and vapour. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Store in a well-ventilated place. Keep container tightly closed.



0.45l, 0.9l,  
2.7l, 10l, 23l



9÷11 m<sup>2</sup>/l



24 h



VAITSOL,  
VAITSPIRTS

